

**EFX[®]**

Solvent Degreaser



FEATURES

- Leaves no residue
- Fast evaporating
- No chlorinated solvents
- Ideal for degreasing metals; safe on most plastics
- Power blast spray instantly removes oil, grease, wax, dirt, tar and other contaminants
- Fast-acting, heavy-duty solvent that degreases and cleans in a single operation

APPLICATIONS

- Air Compressors
- Air Tools
- Bearings
- Chains & Cable Connections
- Cranes
- Engines
- Forklifts
- Machinery
- Gears
- Printing Presses
- Pulleys

PROPERTIES

Appearance / Physical State	Gas/Aerosol Compressed Gas
Odor	Characteristic
Melting / Freezing Point	Not established
Boiling Point / Range	140.9°F (60.5°C)
Vapor Pressure	Not established
Partition Coefficient	>1
Percent volatile	100%
Flammability	lower(%) 1.5%; Upper(%) 9%
Propellant	Petroleum Gases, Liquified
VOC Content	(Aerosol) 86.9 %, (Bulk) 90% per US State and Federal Consumer Product Regulations CARB
Color	Colorless
Flash Point	21.2°F (-6.0°C) Tag Closed Cup -- dispensed liquid
Density	Not available
Evaporation Rate	1.6 (water = 1)
Vapor density	2.8 estimated
Auto-Ignition Temperature	582.8°F (306°C)
Viscosity	< 3 cSt
Specific Gravity	0.65 - 0.68 @ 20°C
Temperature Range	Not available
4-Ball Weld Load	Not applicable

DIRECTIONS

Apply on parts and equipment. Allow solvent to dissolve and remove contaminants. Air dry or wipe with an absorbent cloth for faster drying. If equipment is still dirty or greasy, repeat procedure.

HANDLING

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. (see Section 7 of the SDS)

STORAGE

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. (see Section 7 of the SDS)

DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
01855		55 gal / 208 L	drum	1	
01820	C01820	15 wt oz / 425 g / 588 mL	aerosol	12	15 lbs

**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**800.241.8334 | www.itwprobrands.com

LPS[®], SCRUBS[®], DYKEM[®], Accu-Lube[®], DYMON[®], Spray Nine[®], and Cedar[®] are registered trademarks and Rustlick[™], Diamondkote[™], and MetalMates[™] are trademarks of Illinois Tool Works • All Rights Reserved