



# Electra-X 2.0

## Contact Cleaner



### FEATURES

- Non-Flammable & Non-Conductive: Can be used on or near energized electronic equipment; reduces downtime
- Non-Brominated for improved health risk for increased worker safety and compliance
- Fast Evaporating formulation for quickened clean-up time
- No Rinsing/No Residue
- Inverta Spray Valve for inverted position use
- Economical and Effective degreasing power

### APPLICATIONS

- Contacts
- Controls
- Sensors
- Instrumentation
- Meters
- Printed Circuit Boards

### SPECIFICATIONS AND APPROVALS

- NSF International, K2

### PROPERTIES

<b>Appearance / Physical State</b>	Gas
<b>Color</b>	Clear
<b>Odor</b>	Ether-like.
<b>Boiling Point / Range</b>	<131°F (<55°C)
<b>Flash Point</b>	None
<b>Water Solubility</b>	Slight.
<b>Density</b>	11.06
<b>Specific Gravity</b>	1.33
<b>VOC Content</b>	74%
<b>Propellant</b>	HFO-1234ze, carbon dioxide
<b>Dielectric Strength</b>	43.1 kV

### DIRECTIONS

Spray on parts and equipment. Allow flushing action to dissolve and remove contaminants. Air dry or wipe with an absorbent cloth for faster drying. If equipment is still dirty or greasy, repeat procedure. Use in nonfood handling areas only

### HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not re-use empty containers. Do not breathe gas. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Avoid contact with clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling.

### STORAGE

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°F/122°F. Do not puncture, incinerate or crush. Contents under pressure. Keep away from heat, sparks and open flame. Keep container tightly closed. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

### DISPOSAL

Waste must be disposed of in accordance with any and all applicable environmental control rules and/or regulations.

### AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
07316	12 wt oz / 340 g / 265 mL	aerosol	12	13 lbs



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved