



Electro 140° Contact Cleaner



FEATURES

- Superior Wetting and Penetrating Action
- Controlled Evaporation
- Flash Point 140°F (60°C)
- Non-Conductive and Leaves no Residue
- Safe to use on most surfaces
- Inverta Spray Valve

APPLICATIONS

- Coin Counters & Chutes
- Connectors
- Contacts
- Fluid Systems
- Office Equipment
- Relays and Controls
- Semiconductor Assemblies
- Switches
- Telephone Equipment
- Printed Circuits

SPECIFICATIONS AND APPROVALS

- Ford Motor Co.

PROPERTIES

| | |
|------------------------------------|--|
| Appearance / Physical State | Gas |
| Color | Clear, colorless. |
| Odor | Characteristic. |
| Melting / Freezing Point | N/A |
| Boiling Point / Range | 383°F (195°C) |
| Flash Point | >158°F (>70°C) Tag Closed Cup |
| Evaporation Rate | < 0.1 BuAc |
| Flammability | Lower: 0.6%, Upper: 20.4% (estimated) |
| Vapor Pressure | <0.1 mm Hg @ 20°C |
| Vapor Density | 6.1 (air = 1) |
| Water Solubility | Not soluble in water. |
| Partition Coefficient | >1 |
| Auto-Ignition Temperature | >381.2°F (>194°C) |
| Viscosity | < 3 mm ² /s |
| Heat of Combustion | > 30 kJ/g |
| Specific Gravity | 0.84 - 0.86 @ 20°C (water=1) |
| VOC Content | 0% per U.S. State and Federal Consumer Product Regulations |
| Propellant | Carbon Dioxide |

DIRECTIONS

Hold can 6-8 inches (15-20 cm) away from electronic components and spray directly on surface to clean. May attack certain plastics.

HANDLING

Pressurized container: do not pierce or burn, even after use. Wash thoroughly after handling. Wear eye protection/face protection.

STORAGE

Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50oC/122oF. Keep away from heat, hot surface sparks, open flames, and other ignition sources.

DISPOSAL

Dispose of waste and residues in accordance with local authority requirements.

AVAILABLE PRODUCTS

| Part No. | | Net Contents | Container Type | Units/Case | Approximate Case Weight |
|----------|--------|---------------------------|----------------|------------|-------------------------|
| US | Canada | | | | |
| 00916 | C00916 | 11 wt oz / 312 g / 389 mL | aerosol | 12 | 12 lbs |



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved