



EVR™

Clean Air Solvent Degreaser



FEATURES

- No ozone depleting compounds
- Ideal for cleaning metals
- Excellent alternative to Methyl Ethyl Ketone (MEK)
- Instant cleaning action
- High solvent strength
- Fast Evaporating
- Inverta Spray Valve designed to be sprayed at any angle
- Complies with SCAQMD (South Coast Air Quality Management District) Rule 102
- Complies CARB/OTC (California Air Resources Board/Ozone Transport Commission) Rules

APPLICATIONS

- Bearings
- Brakes
- Controls
- Chains
- Cables
- Gauges
- Gears
- Hand & Power Tools
- Heavy Equipment
- De-energized Cable Connectors
- Instruments
- Machinery
- Metal Prep
- Pulleys

SPECIFICATIONS AND APPROVALS

- NSF International, C1 (Aerosol)

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
05220	C05220	14 wt oz / 397 g/ 492 mL	aerosol	12	15 lbs
05205		5 gal / 18.93 L	pail	1	40 lbs
05255	C05255	55 gal / 208 L	drum	1	369 lbs

PROPERTIES

Appearance / Physical State	Aerosol: Gas, Bulk: Liquid
Color	Clear. Colorless.
Odor	Slight. Orange.
Melting / Freezing Point	Not established
Boiling Point / Range	132.8°F (56°C)
Flash Point	-0.4°F (-18.0°C) Tag Closed Cup
Evaporation Rate	5.6 - 6.1
Flammability	Lower (%) 2.5%; Upper (%) 12.8%
Vapor Pressure	Aerosol: 3452mm Hg@20°C; Bulk: 185 mm Hg @20°C
Auto-Ignition Temperature	869°F (465°C)
Viscosity	14 cSt @ 25°C
Density	6.59
Percent volatile	100%
Specific Gravity	0.79 @ 20°C
VOC Content	0.5% per US State and Federal Consumer Product Regulations
Propellant	Carbon dioxide

DIRECTIONS

Apply on parts and equipment. Allow solvent to dissolve and remove contaminants. Air dry or wipe with an absorbent cloth for faster drying. If equipment is still dirty or greasy, repeat procedure.

HANDLING

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. (see Section 7 of the SDS)

STORAGE

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. (see Section 7 of the SDS)

DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved