



Micro-X NU

Fast Evaporating Contact Cleaner



FEATURES

- Contains NO Chlorinated solvents, safe on plastics
- Removes dirt, flux, moisture, dust, oxides, and other contaminants
- Ideal for electronic and fine parts
- Quick Penetration
- VOC Compliant in all 50 states

APPLICATIONS

- Connectors
- Circuit boards
- Contacts
- Controls
- Fluid Systems
- Instrumentation
- Keyboards

SPECIFICATIONS AND APPROVALS

- NSF International, K2

PROPERTIES

Appearance / Physical State	Aerosol / Gas
Color	Clear/colorless
Odor	Mild
Melting / Freezing Point	-198.4°F (-128°C) estimated
Boiling Point / Range	140.9 °F (60.5°C)
Flash Point	< 1.4°F (< -17.0°C) TCC
Evaporation Rate	<1 BuAc (Ethyl Ether = 1)
Flammability	Flammability limit: Lower = 0.6%, Upper = 7%
Vapor Pressure	352.53 mm Hg @ 38°C
Vapor density	>1 (air = 1)
Water Solubility	<10% by weight
Auto-Ignition Temperature	582.8°F (306°C)
Viscosity	< 3 cSt @ 25°C
Specific Gravity	0.8 - 0.82 @ 20°C
VOC Content	74% (600g/L)
Propellant	HFC-152a

DIRECTIONS

Hold can 6-8 inches (15-20 cm) away and spray directly on surface to remove any contaminants. DO NOT USE ON ENERGIZED ELECTRICAL EQUIPMENT IN OPERATION AND ALLOW SURFACE TO DRY BEFORE RESTART.

HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not re-use empty containers. Do not breathe gas. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Avoid contact with clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling.

STORAGE

Store locked up in a well-ventilated place. Keep container tightly closed. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition.

DISPOSAL

Waste must be disposed of in accordance with any and all applicable environmental control rules and/or regulations.

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
06616	C06616	11 wt oz / 312g / 417 mL	aerosol	12	12 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved