



FEATURES

- Instantly removes brake fluid, grease and oil from brakes
- Improves brake performance
- Helps stop disc brake squeal
- Powerful jet spray and high solvency
 Can be applied without disassembling the brake unit
- No ozone depleting chemicals
- Fast evaporating
- Does not contain chlorinated solvents
- No rinsing • No residue

APPLICATIONS

- Brake backing plates
- Brake cylinders
- Brake drums
- Brake linings Brake rotors
- Disc brake pads

PROPERTIES

Appearance / Physical State	Aerosol / Gas		
Color	Clear/Colorless		
Odor	Ether-like/fruity		
Boiling Point / Range	> 132.8°F (>56°C)		
Flash Point	1.4°F (-17.0 °C) Tag Closed Cup		
Flammability	Flammability limit: lower = 1.2%, upper = 12.8%		
Vapor Pressure	> 75 mm Hg @ 20°C		
Vapor density	~ 3 (air = 1)		
Specific Gravity	0.75 - 0.77 @ 20°C		
Water Solubility	55% w/w		
Percent volatile	100%		
VOC Content	45% per U.S. State and Federal Consumer Product Regulations		
Propellant	Carbon dioxide		

DIRECTIONS

Apply on parts and equipment. Allow solvent to dissolve and remove contaminants. Air dry or wipe with an absorbent cloth for faster drying. If equipment is still dirty of greasy, repeat procedure.

HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. (See Section 7 of the SDS)

STORAGE

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Keep away from heat and sources of ignition. (See Section 7 of the SDS)

DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
03620	15 wt oz / 425 g / 544 mL	aerosol	12	15 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY! 800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved